

# Tesla Industries™ Micro Power Unit Look-Up Table

MPU	D.C. Output Specifications				Battery Specifications					A.C. Input Specifications						Page	
	DC Outputs	Output Voltage	Continuous Amps (AC Required)	Watts	Peak Starting Amps	Amp Hrs.	Watt Hours (No AC)	Watt Hours (With AC)	Recharge Time in Minutes	Vac Single Phase	Vac 3Phase	A.C. Input Amps			Watts		Line Frequency Hz
												Single Phase 120 Vac	Single Phase 240 Vac	Three Phase 208 Vac			
TI78-30 <sub>A</sub>	1	28.8	-	-	-	6.5 <sub>B</sub>	145	-	c	-	-	-	-	-	-	43	
TI59 <sub>A</sub>	1	24	-	-	750	11.5	256	-	c	-	-	-	-	-	-	44	
TI60	1	28.5	10	285	750	11.5	256	541	74	95-260	-	5.5	2.75	-	660	50/60	45
TIUH60	1	28.5	10	285	750	11.5	256	541	74	95-260	-	5.5	2.75	-	660	50/60	46
TI206	1	28.5	10	285	1500	23	512	797	143	95-260	-	5.5	2.75	-	660	50/60	47
TI4676	1	28.5	10	285	1500	23	512	797	143	95-260	-	5.5	2.75	-	660	50/60	48
TI47UH1	1	28.5	10	285	1500	23	512	797	143	95-260	-	5.5	2.75	-	660	50/60	49
TI47407	1	28.5	10	285	1500	23	512	797	143	95-260	-	5.5	2.75	-	660	50/60	50
TI5676	1	28.5	10	285	3000	46	1024	1309	281	95-260	-	5.5	2.75	-	660	50/60	51
TI5679	1	28.5	10	285	3000	46	1024	1309	281	95-260	-	5.5	2.75	-	660	50/60	52
TI58D	1	28.5	10	285	1500	23	512	797	143	95-260	-	5.5	2.75	-	660	50/60	53
TIAH64D	1	28.5	10	285	-	23	512	797	143	95-260	200-260	5.5	2.75	1.85 <sub>D</sub>	660	50/60/400	54

**Notes:** All Tesla Micro Power Units require appropriate line cord for 120 Vac or 240 Vac operations.

A: No onboard charging system.

B: The TI78-30 is a nickel metal hydrate battery.

C: Dependant on charging system.

D: Has the ability to charge batteries off of aircraft power.